



Drawer Type Fiber Patch Panel

Description:

- ◆ Standard: 19" rack mount dimension.
- ◆ Cable entrance: 4 ports, $\varnothing$ 25mm.
- ◆ With cable lead-in, fixation and protection devices. There is enough room for fiber storage, ensure the bending radius is 15 times diameter of the cable.
- ◆ Providing relevant accessories.

Features:

High quality cold rolled sheet forming, electrostatic powder spraying technology, smooth surface, not easy to rust.

High strength sheet metal, long-term using is not easy to deformation.

The edges of metal parts are designed with rounded corners to avoid damage to cables.

The bottom plate is designed with sliding design, for the patch panel already installed on the cabinet, the wiring can be adjusted without removing the patch panel.

Environment:

The operating and storage temperature: - 45 ~ + 80 °C .

Tolerable humidity: <95%.

The voltage resistance between the cable grounding device in the shell and the shell is >3000V(DV), which is tested in 1 minute without breakdown and no flashover.



SHENZHEN FASTLINK COMMUNICATION GROUP CO., LTD

Specification:

Model	PP-SR-24-1U
Type	19inch Rock Mount
Material	1.34mm CRS(Cold Rolled Steel)
Size W*D*H (mm)	482*328*1U
Max capacity (core)	96 24pcs LC quater adapter, 96 pcs SC pigtail
Included accessories	4pcs cable fix accessories, heat shrink tubes, cable ties, number tapes, adapter screws
Product color	Black
Weight	5kg/unit
Working temperature	-40~+85°C
Storage temperature	-40~+85°C
Outer carton dimension (mm)	485*305*425 / 5pcs
Outer Carton Weight (kg)	25 / 5pcs

Application:





SHENZHEN FASTLINK COMMUNICATION GROUP CO., LTD

Detailed Pictures:

